

DEFINITY™ Lenses and DEFINITY SHORT™ Lenses

	CR-39® Material	Trivex® Material	Polycarbonate	High Index 1.60	Thin&Lite® 1.67
Power Range					
Sphere	+6.00 to -10.00 Max combined Sph & cyl -10.00	+6.00 to -10.00 Max combined Sph & cyl -10.00	+4.00 to -7.00 Max combined Sph & cyl -7.00	+8.00 to -12.00 Max combined Sph & cyl -12.00	+10.00 to -12.00 Max combined Sph & cyl -12.00
Cylinder	Up to -4.00	Up to -4.00	Up to -4.00	Up to -4.00	Up to -4.00
Add	+1.00 to +3.00	+1.00 to +3.50 & +4.00	+1.00 to +3.00	+1.00 to +3.00	+1.00 to +3.50 & +4.00
Prism	Up to 6.00 D Max 3.00 D per eye	Up to 6.00 D Max 3.00 D per eye	Up to 6.00 D Max 3.00 D per eye	Up to 6.00 D Max 3.00 D per eye	Up to 6.00 D Max 3.00 D per eye
Options					
Crizal®					
Crizal® Alizé®					
Crizal Alizé with ClearGuard™	AVAILABLE	AVAILABLE	AVAILABLE	AVAILABLE	AVAILABLE
Crizal Sun™					
Transitions® lenses	Gray	Available Q1 2008	Gray and Brown	NA	Gray and Brown
Center Thickness (minus lenses)					
clear	2.0 mm	1.3mm – 1.6 mm	1.3mm – 1.6 mm	1.3mm – 1.6 mm	1.1mm – 1.3 mm
Transitions® lenses	2.0 mm	NA	1.5mm – 1.8 mm	NA	1.1mm – 1.3 mm
Polarized	2.0 mm	NA	NA	NA	NA
AVAILABLE IN POLARIZED®	Gray and Brown +4.00 to -10.00	NA	Available Q1 2008	NA	NA
AR Tints	Grades 0-4 Black, Brown, Gray, Gray-Green Solid tints only	NA	Grades 0-3 Black, Brown, Gray, Gray-Green Solid tints only	NA	NA

DEFINITY minimum fitting height – 18 mm DEFINITY SHORT minimum fitting height – 15 mm